

Anwendungstabelle

ActivationDocument

für den Redispatch 2.0

Version:	1.0
Publikationsdatum:	01.04.2021
Autor:	BDEW

ActivationDocument		SD	Abruf im Aufforderungsfall mit Delta-/Sollwertanweisung					
		Prozessschritt	1	2	3	4	5	6
Häufigkeit	Element/ Attribut	von an	NB	DP	EIV	NB	DP	LF
			DP	EIV	DP -> NB	DP	LF	BKV
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0	1.0		1.0	1.0	1.0
1..1	<i>xsd:sequence</i>							
1..1	DocumentIdentification							
required	<i>v</i>		x	x		x	x	x
1..1	DocumentVersion							
required	<i>v</i>		x	x		x	x	x
1..1	DocumentType							
required	<i>v</i>		A96	A96		A96	A96	A96
1..1	ProcessType							
required	<i>v</i>		A41	A41		A41	A41	A41
1..1	SenderIdentification							
required	<i>v</i>		MP-ID	MP-ID		MP-ID	MP-ID	MP-ID
required	<i>codingScheme</i>		A10 NDE	A10 NDE		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole							
required	<i>v</i>		A18	A39		A18	A39	A06
1..1	ReceiverIdentification							
required	<i>v</i>		MP-ID	MP-ID		MP-ID	MP-ID	MP-ID
required	<i>codingScheme</i>		A10 NDE	A10 NDE		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole							
required	<i>v</i>		A39	A27		A39	A06	A08
1..1	CreationDateTime							
required	<i>v</i>		x	x		x	x	x
1..1	ActivationTimeInterval							
required	<i>v</i>		x	x		x	x	x
0..1	OrderIdentification							
required	<i>v</i>							
0..1	OrderIdentificationVersion							
required	<i>v</i>							
1..2	ActivationTimeSeries							
1..1	<i>xsd:sequence</i>							
1..1	AllocationIdentification							
required	<i>v</i>		x	x		x	x	x
1..1	ResourceProvider							
required	<i>v</i>		MP-ID EIV	MP-ID EIV		MP-ID EIV	MP-ID EIV	MP-ID EIV
required	<i>codingScheme</i>		A10 NDE	A10 NDE		A10 NDE	A10 NDE	A10 NDE
1..1	BusinessType							
required	<i>v</i>		A46 A85	A46 A85		A46 A85	A46 A85	A46 A85
1..1	AcquiringArea							
required	<i>v</i>		10YCB-GERMANY--8	10YCB-GERMANY--8		10YCB-GERMANY--8	10YCB-GERMANY--8	10YCB-GERMANY--8
required	<i>codingScheme</i>		A01	A01		A01	A01	A01
1..1	ConnectingArea							

ActivationDocument		SD	Abruf im Aufforderungsfall mit Delta-/Sollwertanweisung					
		Prozessschritt	1	2	3	4	5	6
Häufigkeit	Element/ Attribut	von an	NB	DP	EIV	NB	DP	LF
			DP	EIV	DP -> NB	DP	LF	BKV
required	v		10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3		10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3
required	<i>codingScheme</i>		A01	A01		A01	A01	A01
1..1	MeasureUnit							
required	v		MAW P1	MAW P1		MAW P1	MAW P1	MAW P1
1..1	Direction							
required	v		A01 A02	A01 A02		A01 A02	A01 A02	A01 A02
1..1	Status							
required	v		A10	A10		A07	A07	A07
1..1	ResourceObject							
required	v		SR-ID	SR-ID		SR-ID	SR-ID	SR-ID
required	<i>codingScheme</i>		NDE	NDE		NDE	NDE	NDE
0..1	SendersDocumentIdentification		[1]	[1]				
	v		x	x				
0..1	SendersDocumentVersion		[1]	[1]				
required	v		x	x				
0..1	SendersDocumentDateTime		[1]	[1]				
required	v		x	x				
0..1	SendersTimeSeriesIdentification		[1]	[1]				
required	v		x	x				
0..1	OriginalSenderIdentification							
required	v			MP-ID NB		MP-ID NB	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>			A10 NDE		A10 NDE	A10 NDE	A10 NDE
0..1	OriginalDocumentIdentification							
required	v			x		x	x	x
0..1	OriginalDocumentVersion							
required	v			x		x	x	x
0..1	OriginalDocumentDateTime							
required	v			x		x	x	x
0..1	OriginalAllocationIdentification							
required	v			x		x	x	x
1..1	Period							
1..1	<i>xsd:sequence</i>							
1..1	TimeInterval							
required	v		x	x		x	x	x
1..1	Resolution							
required	v		PT15M	PT15M		PT15M	PT15M	PT15M
92..100	Interval							

ActivationDocument		SD	Abruf im Aufforderungsfall mit Delta-/Sollwertanweisung					
		Prozessschritt	1	2	3	4	5	6
Häufigkeit	Element/ Attribut	von an	NB	DP	EIV	NB	DP	LF
			DP	EIV	DP -> NB	DP	LF	BKV
1..1	xsd:sequence							
1..1	Pos							
required	v		X	X		X	X	X
1..1	Qty							
required	v		X	X		X	X	X
0..1	Reason							
1..1	xsd:sequence							
1..1	ReasonCode							
required	v		Z04 Z05 Z06	Z04 Z05 Z06		Z04 Z05 Z06	Z04 Z05 Z06	Z04 Z05 Z06
0..1	ReasonText							
required	v							
0..unbounded	Reason							
1..1	xsd:sequence							
1..1	ReasonCode							
required	v							
0..1	ReasonText							
required	v							

ActivationDocument		SD	Abruf im Duldungsfall mit Sollwertanweisung					
		Prozessschritt	1	2	3	4	5	6
Häufigkeit	Element/ Attribut	von an	NB DP	DP EIV	EIV DP -> NB	EIV BTR	DP LF	LF BKV
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0	1.0		1.0	1.0	1.0
1..1	<i>xsd:sequence</i>							
1..1	DocumentIdentification							
required	<i>v</i>		x	x		x	x	x
1..1	DocumentVersion							
required	<i>v</i>		x	x		x	x	x
1..1	DocumentType							
required	<i>v</i>		A96	A96		A96	A96	A96
1..1	ProcessType							
required	<i>v</i>		A41	A41		A41	A41	A41
1..1	SenderIdentification							
required	<i>v</i>		MP-ID	MP-ID		MP-ID	MP-ID	MP-ID
required	<i>codingScheme</i>		A10 NDE	A10 NDE		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole							
required	<i>v</i>		A18	A39		A27	A39	A06
1..1	ReceiverIdentification							
required	<i>v</i>		MP-ID	MP-ID		MP-ID	MP-ID	MP-ID
required	<i>codingScheme</i>		A10 NDE	A10 NDE		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole							
required	<i>v</i>		A39	A27		A21	A06	A08
1..1	CreationDateTime							
required	<i>v</i>		x	x		x	x	x
1..1	ActivationTimeInterval							
required	<i>v</i>		x	x		x	x	x
0..1	OrderIdentification							
required	<i>v</i>							
0..1	OrderIdentificationVersion							
required	<i>v</i>							
1..2	ActivationTimeSeries							
1..1	<i>xsd:sequence</i>							
1..1	AllocationIdentification							
required	<i>v</i>		x	x		x	x	x
1..1	ResourceProvider							
required	<i>v</i>		MP-ID EIV	MP-ID EIV		MP-ID EIV	MP-ID EIV	MP-ID EIV
required	<i>codingScheme</i>		A10 NDE	A10 NDE		A10 NDE	A10 NDE	A10 NDE
1..1	BusinessType							
required	<i>v</i>		A85	A85		A85	A85	A85
1..1	AcquiringArea							
required	<i>v</i>		10YCB-GERMANY--8	10YCB-GERMANY--8		10YCB-GERMANY--8	10YCB-GERMANY--8	10YCB-GERMANY--8
required	<i>codingScheme</i>		A01	A01		A01	A01	A01
1..1	ConnectingArea							

ActivationDocument		SD	Abruf im Duldungsfall mit Sollwertanweisung					
		Prozessschritt	1	2	3	4	5	6
Häufigkeit	Element/ Attribut	von an	NB DP	DP EIV	EIV DP -> NB	EIV BTR	DP LF	LF BKV
required	v		10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3		10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3
required	<i>codingScheme</i>		A01	A01		A01	A01	A01
1..1	MeasureUnit							
required	v		P1	P1		P1	P1	P1
1..1	Direction							
required	v		A01 A02	A01 A02		A01 A02	A01 A02	A01 A02
1..1	Status							
required	v		A07	A07		A07	A07	A07
1..1	ResourceObject							
required	v		SR-ID	SR-ID		SR-ID	SR-ID	SR-ID
required	<i>codingScheme</i>		NDE	NDE		NDE	NDE	NDE
0..1	SendersDocumentIdentification							
	v							
0..1	SendersDocumentVersion							
required	v							
0..1	SendersDocumentDateTime							
required	v							
0..1	SendersTimeSeriesIdentification							
required	v							
0..1	OriginalSenderIdentification							
required	v			MP-ID NB		MP-ID NB	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>			A10 NDE		A10 NDE	A10 NDE	A10 NDE
0..1	OriginalDocumentIdentification							
required	v			x		x	x	x
0..1	OriginalDocumentVersion							
required	v			x		x	x	x
0..1	OriginalDocumentDateTime							
required	v			x		x	x	x
0..1	OriginalAllocationIdentification							
required	v			x		x	x	x
1..1	Period							
1..1	xsd:sequence							
1..1	TimeInterval							
required	v		x	x		x	x	x
1..1	Resolution							
required	v		PT15M	PT15M		PT15M	PT15M	PT15M
92..100	Interval							

ActivationDocument		SD	Abruf im Duldungsfall mit Sollwertanweisung					
		Prozessschritt	1	2	3	4	5	6
Häufigkeit	Element/ Attribut	von	NB	DP	EIV	EIV	DP	LF
		an	DP	EIV	DP -> NB	BTR	LF	BKV
1..1	xsd:sequence							
1..1	Pos							
required	v		x	x		x	x	x
1..1	Qty							
required	v		x	x		x	x	x
0..1	Reason							
1..1	xsd:sequence							
1..1	ReasonCode							
required	v		Z04 Z05 Z06	Z04 Z05 Z06		Z04 Z05 Z06	Z04 Z05 Z06	Z04 Z05 Z06
0..1	ReasonText							
required	v							
0..unbounded	Reason							
1..1	xsd:sequence							
1..1	ReasonCode							
required	v							
0..1	ReasonText							
required	v							

ActivationDocument		SD	Übermittlung des Abrufs einer steuerbaren Ressource an anweisenden NB mit DP				Übermittlung des Abrufs einer steuerbaren	
		Prozessschritt	1	2	3	4	1	2
Häufigkeit	Element/ Attribut	von	NB (anfNB)	DP	NB (anwNB)	DP	NB (anfNB)	NB (anwNB)
		an	DP	NB (anwNB)	DP	NB (anfNB)	NB (anwNB)	NB (anfNB)
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0	1.0	1.0	1.0	1.0	1.0
1..1	<i>xsd:sequence</i>							
1..1	DocumentIdentification							
required	<i>v</i>		x	x	x	x	x	x
1..1	DocumentVersion							
required	<i>v</i>		x	x	x	x	x	x
1..1	DocumentType							
required	<i>v</i>		A96	A96	A41	A41	A96	A41
1..1	ProcessType							
required	<i>v</i>		A41	A41	A41	A41	A41	A41
1..1	SenderIdentification							
required	<i>v</i>		MP-ID	MP-ID	MP-ID	MP-ID	MP-ID	MP-ID
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole							
required	<i>v</i>		A18	A39	A18	A39	A18	A18
1..1	ReceiverIdentification							
required	<i>v</i>		MP-ID	MP-ID	MP-ID	MP-ID	MP-ID	MP-ID
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole							
required	<i>v</i>		A39	A18	A39	A18	A18	A18
1..1	CreationDateTime							
required	<i>v</i>		x	x	x	x	x	x
1..1	ActivationTimeInterval							
required	<i>v</i>		x	x	x	x	x	x
0..1	OrderIdentification							
required	<i>v</i>				x	x		x
0..1	OrderIdentificationVersion							
required	<i>v</i>				x	x		x
1..2	ActivationTimeSeries							
1..1	<i>xsd:sequence</i>							
1..1	AllocationIdentification							
required	<i>v</i>		x	x	x	x	x	x
1..1	ResourceProvider							
required	<i>v</i>		MP-ID EIV	MP-ID EIV	MP-ID EIV	MP-ID EIV	MP-ID EIV	MP-ID EIV
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	BusinessType							
required	<i>v</i>		A46 A85	A46 A85	A46 A85	A46 A85	A46 A85	A46 A85
1..1	AcquiringArea							
required	<i>v</i>		10YCB-GERMANY--8	10YCB-GERMANY--8	10YCB-GERMANY--8	10YCB-GERMANY--8	10YCB-GERMANY--8	10YCB-GERMANY--8
required	<i>codingScheme</i>		A01	A01	A01	A01	A01	A01
1..1	ConnectingArea							

ActivationDocument		SD	Übermittlung des Abrufs einer steuerbaren Ressource an anweisenden NB mit DP				Übermittlung des Abrufs einer steuerbaren	
		Prozessschritt	1	2	3	4	1	2
Häufigkeit	Element/ Attribut	von	NB (anfNB)	DP	NB (anwNB)	DP	NB (anfNB)	NB (anwNB)
		an	DP	NB (anwNB)	DP	NB (anfNB)	NB (anfNB)	NB (anfNB)
required	v		10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3
required	<i>codingScheme</i>		A01	A01	A01	A01	A01	A01
1..1	MeasureUnit							
required	v		MAW P1	MAW P1	MAW P1	MAW P1	MAW P1	MAW P1
1..1	Direction							
required	v		A01 A02	A01 A02	A01 A02	A01 A02	A01 A02	A01 A02
1..1	Status							
required	v		A10	A10	A06	A06	A10	A06
1..1	ResourceObject							
required	v		SR-ID SG-ID	SR-ID SG-ID	SR-ID SG-ID	SR-ID SG-ID	SR-ID SG-ID	SR-ID SG-ID
required	<i>codingScheme</i>		NDE	NDE	NDE	NDE	NDE	NDE
0..1	SendersDocumentIdentification		[1]	[1]			[1]	
	v		x	x			x	
0..1	SendersDocumentVersion		[1]	[1]			[1]	
required	v		x	x			x	
0..1	SendersDocumentDateTime		[1]	[1]			[1]	
required	v		x	x			x	
0..1	SendersTimeSeriesIdentification		[1]	[1]			[1]	
required	v		x	x			x	
0..1	OriginalSenderIdentification							
required	v			MP-ID anf. NB		MP-ID anw. NB		
required	<i>codingScheme</i>			A10 NDE		A10 NDE		
0..1	OriginalDocumentIdentification							
required	v			x		x		
0..1	OriginalDocumentVersion							
required	v			x		x		
0..1	OriginalDocumentDateTime							
required	v			x		x		
0..1	OriginalAllocationIdentification							
required	v			x		x		
1..1	Period							
1..1	xsd:sequence							
1..1	TimeInterval							
required	v		x	x	x	x	x	x
1..1	Resolution							
required	v		PT15M	PT15M	PT15M	PT15M	PT15M	PT15M
92..100	Interval							

ActivationDocument		SD	Übermittlung des Abrufs einer steuerbaren Ressource an anweisenden NB mit DP				Übermittlung des Abrufs einer steuerbaren	
		Prozessschritt	1	2	3	4	1	2
Häufigkeit	Element/ Attribut	von	NB (anfNB)	DP	NB (anwNB)	DP	NB (anfNB)	NB (anwNB)
		an	DP	NB (anwNB)	DP	NB (anfNB)	NB (anfNB)	NB (anfNB)
1..1	xsd:sequence							
1..1	Pos							
required	v		x	x	x	x	x	x
1..1	Qty							
required	v		x	x	x	x	x	x
0..1	Reason							
1..1	xsd:sequence							
1..1	ReasonCode							
required	v		Z04 Z05 Z06	Z04 Z05 Z06	A44 A95	A44 A94	Z04 Z05 Z06	A44 A94
0..1	ReasonText							
required	v				o	o		o
0..unbounded	Reason							
1..1	xsd:sequence							
1..1	ReasonCode							
required	v				A57 A95 A96	A57 A95 A96		A57 A95 A96
0..1	ReasonText							
required	v							o

ActivationDocument		SD	Abruf für eine Cluster-Ressource mit DP				Abruf für eine Cluster-Ressource ohne DP	
		Prozessschritt	1	2	3	4	1	2
Häufigkeit	Element/ Attribut	von	NB (anfNB)	DP	NB (anwNB)	DP	NB (anfNB)	NB (anwNB)
		an	DP	NB (anwNB)	DP	NB (anfNB)	NB (anfNB)	NB (anfNB)
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0	1.0	1.0	1.0	1.0	1.0
1..1	<i>xsd:sequence</i>							
1..1	DocumentIdentification							
required	<i>v</i>		x	x	x	x	x	x
1..1	DocumentVersion							
required	<i>v</i>		x	x	x	x	x	x
1..1	DocumentType							
required	<i>v</i>		A96	A96	A41	A41	A96	A41
1..1	ProcessType							
required	<i>v</i>		A41	A41	A41	A41	A41	A41
1..1	SenderIdentification							
required	<i>v</i>		MP-ID	MP-ID	MP-ID	MP-ID	MP-ID	MP-ID
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole							
required	<i>v</i>		A18	A39	A18	A39	A18	A18
1..1	ReceiverIdentification							
required	<i>v</i>		MP-ID	MP-ID	MP-ID	MP-ID	MP-ID	MP-ID
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole							
required	<i>v</i>		A39	A18	A39	A18	A18	A18
1..1	CreationDateTime							
required	<i>v</i>		x	x	x	x	x	x
1..1	ActivationTimeInterval							
required	<i>v</i>		x	x	x	x	x	x
0..1	OrderIdentification							
required	<i>v</i>				x	x		x
0..1	OrderIdentificationVersion							
required	<i>v</i>				x	x		x
1..2	ActivationTimeSeries							
1..1	<i>xsd:sequence</i>							
1..1	AllocationIdentification							
required	<i>v</i>		x	x	x	x	x	x
1..1	ResourceProvider							
required	<i>v</i>		MP-ID EIV	MP-ID EIV	MP-ID EIV	MP-ID EIV	MP-ID EIV	MP-ID EIV
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	BusinessType							
required	<i>v</i>		A46	A46	A46	A46	A46	A46
1..1	AcquiringArea							
required	<i>v</i>		10YCB-GERMANY--8	10YCB-GERMANY--8	10YCB-GERMANY--8	10YCB-GERMANY--8	10YCB-GERMANY--8	10YCB-GERMANY--8
required	<i>codingScheme</i>		A01	A01	A01	A01	A01	A01
1..1	ConnectingArea							

ActivationDocument		SD	Abruf für eine Cluster-Ressource mit DP				Abruf für eine Cluster-Ressource ohne DP	
		Prozessschritt	1	2	3	4	1	2
Häufigkeit	Element/ Attribut	von	NB (anfNB)	DP	NB (anwNB)	DP	NB (anfNB)	NB (anfNB)
		an	DP	NB (anwNB)	DP	NB (anfNB)	NB (anfNB)	NB (anfNB)
required	v		10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3
required	<i>codingScheme</i>		A01	A01	A01	A01	A01	A01
1..1	MeasureUnit							
required	v		MAW	MAW	MAW	MAW	MAW	MAW
1..1	Direction							
required	v		A01 A02	A01 A02	A01 A02	A01 A02	A01 A02	A01 A02
1..1	Status							
required	v		A10	A10	A06	A06	A10	A06
1..1	ResourceObject							
required	v		CR-ID	CR-ID	CR-ID	CR-ID	CR-ID	CR-ID
required	<i>codingScheme</i>		NDE	NDE	NDE	NDE	NDE	NDE
0..1	SendersDocumentIdentification		[1]	[1]			[1]	
	v		x	x			x	
0..1	SendersDocumentVersion		[1]	[1]			[1]	
required	v		x	x			x	
0..1	SendersDocumentDateTime		[1]	[1]			[1]	
required	v		x	x			x	
0..1	SendersTimeSeriesIdentification		[1]	[1]			[1]	
required	v		x	x			x	
0..1	OriginalSenderIdentification							
required	v			MP-ID anf. NB		MP-ID anw. NB		
required	<i>codingScheme</i>			A10 NDE		A10 NDE		
0..1	OriginalDocumentIdentification							
required	v			x		x		
0..1	OriginalDocumentVersion							
required	v			x		x		
0..1	OriginalDocumentDateTime							
required	v			x		x		
0..1	OriginalAllocationIdentification							
required	v			x		x		
1..1	Period							
1..1	xsd:sequence							
1..1	TimeInterval							
required	v		x	x	x	x	x	x
1..1	Resolution							
required	v		PT15M	PT15M	PT15M	PT15M	PT15M	PT15M
92..100	Interval							

ActivationDocument		SD Prozessschritt	Abruf für eine Cluster-Ressource mit DP				Abruf für eine Cluster-Ressource ohne DP	
			1	2	3	4	1	2
Häufigkeit	Element/ Attribut	von	NB (anfNB)	DP	NB (anwNB)	DP	NB (anfNB)	NB (anfNB)
		an	DP	NB (anwNB)	DP	NB (anfNB)	NB (anfNB)	NB (anfNB)
1 .. 1	xsd:sequence							
1 .. 1	Pos							
required	v		x	x	x	x	x	x
1 .. 1	Qty							
required	v		x	x	x	x	x	x
0 .. 1	Reason							
1 .. 1	xsd:sequence							
1 .. 1	ReasonCode							
required	v		Z04 Z05 Z06	Z04 Z05 Z06	A44 A95	A44 A94	Z04 Z05 Z06	A44 A94
0 .. 1	ReasonText							
required	v				o	o		o
0 .. unbounded	Reason							
1 .. 1	xsd:sequence							
1 .. 1	ReasonCode							
required	v				A57 A95 A96	A57 A95 A96		A57 A95 A96
0 .. 1	ReasonText							
required	v				o	o		o

ActivationDocument		SD	Abruf für eine Steuergruppe mit DP				Abruf für eine Steuergruppe ohne DP	
		Prozessschritt	1	2	3	4	1	2
Häufigkeit	Element/ Attribut	von	NB (anfNB)	DP	NB (anwNB)	DP	NB (anfNB)	NB (anwNB)
		an	DP	NB (anwNB)	DP	NB (anfNB)	NB (anwNB)	NB (anfNB)
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0	1.0	1.0	1.0	1.0	1.0
1..1	<i>xsd:sequence</i>							
1..1	DocumentIdentification							
required	<i>v</i>		x	x	x	x	x	x
1..1	DocumentVersion							
required	<i>v</i>		x	x	x	x	x	x
1..1	DocumentType							
required	<i>v</i>		A96	A96	A41	A41	A96	A41
1..1	ProcessType							
required	<i>v</i>		A41	A41	A41	A41	A41	A41
1..1	SenderIdentification							
required	<i>v</i>		MP-ID	MP-ID	MP-ID	MP-ID	MP-ID	MP-ID
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole							
required	<i>v</i>		A18	A39	A18	A39	A18	A18
1..1	ReceiverIdentification							
required	<i>v</i>		MP-ID	MP-ID	MP-ID	MP-ID	MP-ID	MP-ID
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole							
required	<i>v</i>		A39	A18	A39	A18	A18	A18
1..1	CreationDateTime							
required	<i>v</i>		x	x	x	x	x	x
1..1	ActivationTimeInterval							
required	<i>v</i>		x	x	x	x	x	x
0..1	OrderIdentification							
required	<i>v</i>				x	x		x
0..1	OrderIdentificationVersion							
required	<i>v</i>				x	x		x
1..2	ActivationTimeSeries							
1..1	<i>xsd:sequence</i>							
1..1	AllocationIdentification							
required	<i>v</i>		x	x	x	x	x	x
1..1	ResourceProvider							
required	<i>v</i>		MP-ID EIV	MP-ID EIV	MP-ID EIV	MP-ID EIV	MP-ID EIV	MP-ID EIV
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	BusinessType							
required	<i>v</i>		A46 A85	A46 A85	A46 A85	A46 A85	A46 A85	A46 A85
1..1	AcquiringArea							
required	<i>v</i>		10YCB-GERMANY--8	10YCB-GERMANY--8	10YCB-GERMANY--8	10YCB-GERMANY--8	10YCB-GERMANY--8	10YCB-GERMANY--8
required	<i>codingScheme</i>		A01	A01	A01	A01	A01	A01
1..1	ConnectingArea							

ActivationDocument		SD	Abruf für eine Steuergruppe mit DP				Abruf für eine Steuergruppe ohne DP	
		Prozessschritt	1	2	3	4	1	2
Häufigkeit	Element/ Attribut	von an	NB (anfNB) DP	DP NB (anwNB)	NB (anwNB) DP	DP NB (anfNB)	NB (anfNB) NB (anwNB)	NB (anfNB) NB (anwNB)
required	v		10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3	10YDE-VE-----2 10YDE-RWENET--- 10YDE-EON-----1 10YDE-ENBW----N 10YFLENSBURG---3
required	<i>codingScheme</i>		A01	A01	A01	A01	A01	A01
1..1	MeasureUnit							
required	v		MAW P1	MAW P1	MAW P1	MAW P1	MAW P1	MAW P1
1..1	Direction							
required	v		A01 A02	A01 A02	A01 A02	A01 A02	A01 A02	A01 A02
1..1	Status							
required	v		A10	A10	A06	A06	A10	A06
1..1	ResourceObject							
required	v		SG-ID	SG-ID	SG-ID	SG-ID	SG-ID	SG-ID
required	<i>codingScheme</i>		NDE	NDE	NDE	NDE	NDE	NDE
0..1	SendersDocumentIdentification		[1]	[1]			[1]	
	v		x	x			x	
0..1	SendersDocumentVersion		[1]	[1]			[1]	
required	v		x	x			x	
0..1	SendersDocumentDateTime		[1]	[1]			[1]	
required	v		x	x			x	
0..1	SendersTimeSeriesIdentification		[1]	[1]			[1]	
required	v		x	x			x	
0..1	OriginalSenderIdentification							
required	v			MP-ID anf. NB		MP-ID anw. NB		
required	<i>codingScheme</i>			A10 NDE		A10 NDE		
0..1	OriginalDocumentIdentification							
required	v			x		x		
0..1	OriginalDocumentVersion							
required	v			x		x		
0..1	OriginalDocumentDateTime							
required	v			x		x		
0..1	OriginalAllocationIdentification							
required	v			x		x		
1..1	Period							
1..1	xsd:sequence							
1..1	TimeInterval							
required	v		x	x	x	x	x	x
1..1	Resolution							
required	v		PT15M	PT15M	PT15M	PT15M	PT15M	PT15M
92..100	Interval							

ActivationDocument		SD	Abruf für eine Steuergruppe mit DP				Abruf für eine Steuergruppe ohne DP	
		Prozessschritt	1	2	3	4	1	2
Häufigkeit	Element/ Attribut	von	NB (anfNB)	DP	NB (anwNB)	DP	NB (anfNB)	NB (anwNB)
		an	DP	NB (anwNB)	DP	NB (anfNB)	NB (anfNB)	NB (anfNB)
1..1	xsd:sequence							
1..1	Pos							
required	v		X	X	X	X	X	X
1..1	Qty							
required	v		X	X	X	X	X	X
0..1	Reason							
1..1	xsd:sequence							
1..1	ReasonCode							
required	v		Z04 Z05 Z06	Z04 Z05 Z06	A44 A95	A44 A94	Z04 Z05 Z06	A44 A94
0..1	ReasonText							
required	v				o	o		o
0..unbounded	Reason							
1..1	xsd:sequence							
1..1	ReasonCode							
required	v				A57 A95 A96	A57 A95 A96		A57 A95 A96
0..1	ReasonText							
required	v				o	o		o

Fußnoten

Fußnote	Hinweis
[1]	Elemente <i>SendersDocumentIdentification</i> und <i>SendersDocumentVersion</i> sind nur im Planwertmodell im Aufforderungsfall mit Deltaanweisung (<i>BusinessType</i> A46) mit Status A10 zu benutzen.